




Website: www.FirstChoiceMarineSupply.com Email: Sales@FirstChoiceMarineSupply.com



RATED CAPACITIES BASED ON DESIGN FACTOR OF 5 TO 1

2 - LEG BRIDLE WIRE ROPE SLINGS - WITH EYE HOIST HOOKS					
ROPE DIA.	EIPS CAPACITIES (TONS) WITH EYE HOIST HOOKS			ALLOY OBLONG MASTER LINK DIA.	MINIMUM SLING LENGTH
	30°	45°	60°		
1/4	0.65	0.92	1.	1/2	1'3"
3/8	1.4	2	2.5	1/2	1'8"
1/2	2.5	3.6	4.4	3/4	2'
5/8	3.9	5.5	6.8	1	2'4"
3/4	5.6	7.9	9.7	1	2'9"
7/8	7.6	11	13	1-1/4	3'3"
1	9.8	14	17	1-1/2	3'6"
1-1/8	12	17	21	1-1/2	4'
1-1/4	15	21	26	1-3/4	4'6"
1-3/8	18	25	31	1-3/4	5'
1-1/2	21	30	37	2	5'6"
1-3/4	28	40	49	2-1/4	6'6"
2	37	52	63	2-1/2	8'
2-1/4	44	63	77	2-3/4	8'9"




Website: www.FirstChoiceMarineSupply.com Email: Sales@FirstChoiceMarineSupply.com



RATED CAPACITIES BASED ON DESIGN FACTOR OF 5 TO 1

4 - LEG BRIDLE WIRE ROPE SLINGS - WITH EYE HOIST HOOKS					
ROPE DIA.	EIPS CAPACITIES (TONS) WITH EYE HOIST HOOKS			ALLOY OBLONG MASTER LINK DIA.	MINIMUM SLING LENGTH
	30°	45°	60°		
1/4	1.3	1.8	2.2	3/4	1'3"
3/8	2.9	4.1	5	3/4	1'8"
1/2	5.1	7.1	8.8	1	2'
5/8	7.8	11	14	1-1/4	2'4"
3/4	11	16	19	1-1/2	2'9"
7/8	15	21	26	1-3/4	3'3"
1	20	28	34	2	3'6"
1-1/8	24	34	42	2	4'
1-1/4	30	42	51	2-1/4 (PEAR LINK)	4'6"
1-3/8	36	50	62	2-3/4 (PEAR LINK)	5'
1-1/2	42	60	73	2-3/4 (PEAR LINK)	5'6"
1-3/4	57	80	98	2-3/4 (PEAR LINK)	6'6"
2	73	104	127	3-1/4 (PEAR LINK)	8'

Website: www.FirstChoiceMarineSupply.com Email: Sales@FirstChoiceMarineSupply.com



RATED CAPACITIES BASED ON DESIGN FACTOR OF 5 TO 1

STANDARD EYE & EYE WIRE ROPE SLINGS								
ROPE DIA.	EIPS CAPACITIES (TONS)			STANDARD EYE DIMENSIONS (W" x L")		THIMBLED EYE DIMENSIONS (W" x L")		MIN. EYE & EYE SLING LENGTH
	VERTICAL	CHOKER HITCH	VERTICAL BASKET*					
1/4	0.65	0.48	1.3	2	4	7/8	1-5/8	1'6"
5/16	1	0.74	2	2-1/2	5	1-1/16	1-7/8	1'9"
3/8	1.4	1.1	2.9	3	6	1-1/8	2-1/8	2'
7/16	1.9	1.4	3.9	3-1/2	7	1-1/2	2-3/4	2'3"
1/2	2.5	1.9	5.1	4	8	1-1/2	2-3/4	2'6"
9/16	3.2	2.4	6.4	4-1/2	8	1-1/2	2-3/4	2'9"
5/8	3.9	2.9	7.8	5	10	1-3/4	3-1/4	3'
3/4	5.6	4.1	11	6	12	2	3-3/4	3'6"
7/8	7.6	5.6	15	7	14	2-1/4	4-1/4	4'
1	9.8	7.2	20	8	16	2-1/2	4-1/2	4'6"
1-1/8	12	9.1	24	9	18	2-7/8	5-1/8	5'
1-1/4	15	11	30	10	20	2-7/8	5-1/8	5'6"
1-3/8	18	13	36	11	22	3-1/2	6-1/4	6'
1-1/2	21	16	42	12	24	3-1/2	6-1/4	7'
1-3/4	28	21	57	14	28	4-1/2	9	8'
2	37	28	73	16	32	6	12	9'
2-1/4	44	35	89	18	36	7	14	10'

*RATED CAPACITIES FOR BASKET HITCH BASED ON D/D RATIO OF 25